

Makita[®]

mit



maktec[®]
by Makita.



M4000 CB: 85 MT Series

ELECTRIC BLOWER
 Tool Available in:
 * M4000B
 * M4000M



Continuous rating input	530W
Air volume	1.2-2.9 m ³ /min
No Load Speed (RPM)	8,500 - 16,000
Vibration Level	Operation w/o Load: 2.5 m/s ² or less
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Dimensions (L x W x H)	427x161x212 mm (16.34"x6.31"x8.31")
Net weight	1.5 kg (3.4 lbs)
Power supply cord	2.0 m (6.6 ft)



M0600 CB: 64 MT Series

ELECTRIC DRILL
 Tool Available in:
 * M0600B
 * M0600M



Continuous rating input	350W
Capacity	Steel: 10 mm (3/8") Wood: 20 mm (13/16")
No Load Speed (RPM)	0 - 3,000
Vibration Level	Drilling Into Metal: 3.0 m/s ²
Sound Pressure Level	77 dB(A)
Sound Power Level	230x66x176 mm (9.1"x2.6"x6.9")
Dimensions (L x W x H)	
Net weight	1.2 kg (2.6 lbs)
Power supply cord	2.0 m (6.6 ft)



M6200 CB: 303 MT Series

ELECTRIC DRILL
 Tool Available in:
 * M6200B



Continuous rating input	800W
Capacity	Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
No Load Speed (RPM)	0 - 700
Vibration Level	Drilling Into Metal: 2.5 m/s ² or less
Sound Pressure Level	84 dB(A)
Sound Power Level	95 dB(A)
Dimensions (L x W x H)	267x83x388 mm (10.51"x3.27"x15.28")
Net weight	2.7 - 2.8 kg (6.0 - 6.2 lbs)
Power supply cord	2.0 m (6.6 ft)



M6202 CB: 64 MT Series

ELECTRIC DRILL
 Tool Available in:
 * M6202M



Continuous Rating Input	580W
Capacity	Steel: 13 mm (1/2") Wood: 25 mm (1")
Chuck Capacity	1.5 - 13 mm (1/16" - 1/2")
No Load Speed (RPM)	2,000
Dimensions (L x W x H)	283 x 69 x 178 mm (11.18 x 2.72 x 7")
Net weight	2 kg (4.4 lbs.)
Power supply cord	2.0 m (6.6 ft)



M6500 CB: 64 MT Series

ELECTRIC HIGH SPEED DRILL
 Tool Available in:
 * M6500B
 * M6500M



Continuous Rating Input	230W
Capacity	Steel: 6.5 mm (1/4") Wood: 9 mm (11/32")
Chuck Capacity	0.5 - 6.5 mm (1/64" - 1/4")
No Load Speed (RPM)	4,500
Vibration Level	Drilling into Metal: 2.5 m/s ²
Sound Pressure Level	72 dB(A)
Dimensions (L x W x H)	200 x 63 x 164 mm (7.78 x 2.48 x 6.46")
Net weight	0.92 kg (2 lbs.)
Power supply cord	2.0 m (6.6 ft)



M0800 CB: 85 MT Series

ELECTRIC HAMMER DRILL
 Tool Available in:
 * M0800M



Continuous rating input	500W
Capacity	Concrete: 10 mm (3/8") Steel: 10 mm (3/8") Wood: 20 mm (13/16")
Blows Per Minute (BPM)	0 - 48,000
No Load Speed (RPM)	0 - 3,200
Dimensions (L x W x H)	254x69x195 mm (10"x2.7"x7.7")
Net weight	1.6 kg (3.4 lbs)
Power supply cord	2.0 m (6.6 ft)



M0801 CB: 85 MT Series

ELECTRIC HAMMER DRILL
 Tool Available in:
 * M0801B



Continuous rating input	500W
Capacity	Concrete: 16 mm (5/8") Steel: 13 mm (1/2") Wood: 20 mm (13/16")
Blows Per Minute (BPM)	0 - 48,000
No Load Speed (RPM)	0 - 3,200
Vibration Level	Hammer Drilling Into Concrete: 14.5 m/s ²
Sound Pressure Level	Drilling Into Metal: 4.0 m/s ²
Sound Power Level	94 dB(A)
Dimensions (L x W x H)	261x69x195 mm (10.3"x2.7"x7.7")
Net weight	1.7 kg (3.7 lbs)
Power supply cord	2.0 m (6.6 ft)



M8103 CB: 85 MT Series

ELECTRIC HAMMER DRILL
 Tool Available in:
 * M8103KX2B
 * M8103KX2M



Continuous Rating Input	430W
Capacity	Concrete: 13 mm (1/2") Steel: 13 mm (1/2") Wood: 18 mm (11/16")
Chuck Capacity	1.5 - 13 mm (1/16" - 1/2")
Blows Per Minute (BPM)	0 - 33,000
No Load Speed (RPM)	0 - 3,000
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Dimensions (L x W x H)	255 x 72 x 193 mm (10.04 x 2.83 x 7.6")
Net weight	1.8 kg (3.9 lbs.)
Power supply cord	2.0 m (6.6 ft)



M8700

CB: 459 MT Series

ELECTRIC ROTARY HAMMER

Tool Available in:
* M8700B
* M8700M



Continuous Rating Input	710W
Impact Energy	EPTA-Procedure 05/2009: 1.9 J
Capacity	Concrete: 22 mm (7/8") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Masonry: 22 mm (7/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,350
No Load Speed (RPM)	0 - 1,100
Sound Pressure Level	90 dB(A)
Vibration Level	101 dB(A)
Dimensions (L x W x H)	362 x 71 x 194 mm (14-1/4 x 2-13/16 x 7-5/8")
Net weight	2.5 - 2.9 kg (5.6 - 6.4 lbs.)
Power supply cord	4.0 m (13.1 ft.)



M8600

CB: 105 MT Series

ELECTRIC DEMOLITION HAMMER

Tool Available in:
* M8600B
* M8600M



Continuous Rating Input	900W
Impact Energy	7.2 J
Blows Per Minute (BPM)	2,900
Vibration Level	Chiselling Function w/ Side Grip: 16.5 m/s ²
Sound Pressure Level	95 dB(A)
Sound Power Level	106 dB(A)
Dimensions (L x W x H)	406 x 99 x 232 mm (16 x 3-7/8 x 9-1/8")
Net weight	5.4 kg (12 lbs.)
Power supply cord	2.5 m (8.2 ft.)



M2401

CB: 203 MT Series

ELECTRIC PORTABLE CUT-OFF

Tool Available in:
* M2401B
* M2401M



Continuous rating input	2,000W
Wheel Diameter	355 mm (14")
No Load Speed (RPM)	3,800
Capacity at 90°	Round: 127 mm (5") Rectangular: 102x194 mm (4"x7-5/8") Rectangular: 70x233 mm (2-3/4"x9-1/8")
Capacity at 45°	Round: 127 mm (5") Rectangular: 115x103 mm (4-1/2"x4-1/16")
Vibration Level	3.0 m/s ²
Sound Pressure Level	100 dB(A)
Sound Power Level	111 dB(A)
Dimensions (L x W x H)	500x280x620 mm (19-3/4"x11"x24-3/8")
Net weight	13.7 kg (30.2 lbs.)
Power supply cord	2.5 m (8.2 ft.)



M2402

CB: 203 MT Series

ELECTRIC PORTABLE CUT-OFF

Tool Available in:
* M2402B



Continuous rating input	2,200W
Wheel Diameter	355 mm (14")
No Load Speed (RPM)	3,800
Capacity at 90°	Round: 127 mm (5") Rectangular: 102x194 mm (4"x7-5/8") Rectangular: 70x233 mm (2-3/4"x9-1/8")
Capacity at 45°	Round: 127 mm (5") Rectangular: 115x103 mm (4-1/2"x4-1/16")
Vibration Level	4.5 m/s ²
Sound Pressure Level	98 dB(A)
Sound Power Level	108 dB(A)
Dimensions (L x W x H)	490x280x610 mm (19-1/4x11"x24")
Net weight	14.5 kg (32.0 lbs.)
Power supply cord	2.0 m (6.6 ft.)



M5801

CB: 303 MT Series

ELECTRIC CIRCULAR SAW

Tool Available in:
* M5801B



Continuous rating input	1,050W
Blade Diameter	185 mm (7-1/4")
Max Cutting Capacity	90°: 66 mm (2-5/8") 45°: 44 mm (1-3/4")
No Load Speed (RPM)	4,900
Vibration Level	Cutting Wood: 2.5 m/s ²
Dimensions (L x W x H)	284x231x243 mm (11-1/8"x9-1/8"x9-9/16")
Net weight	3.5 kg (7.7 lbs)
Power supply cord	2.0 m (6.6 ft.)



M4500

CB: 303 MT Series

ELECTRIC RECIPRO SAW

Tool Available in:
* M4500B



Continuous rating input	1,010W
Length of Stroke	28 mm (1-1/8")
Strokes Per Minute (SPM)	0 - 2,800
Capacity	Pipe: 130 mm (5-1/8") Wood: 255 mm (10")
Vibration Level	Cutting Boards: 19.5 m/s ² Cutting Wooden Beams: 22.0 m/s ²
Sound Pressure Level	88 dB(A)
Sound Power Level	99 dB(A)
Dimensions (L x W x H)	457x98x174 mm (18"x3-7/8"x6-7/8")
Net weight	3.1 kg (6.9 lbs)
Power supply cord	2.0 m (6.6 ft.)



M4301

CB: 64 MT Series

ELECTRIC JIG SAW

Tool Available in:
* M4301B
* M4301M



Continuous rating input	450W
Max Cutting Capacity at 90°	Wood: 65 mm (2-9/16") Steel: 6 mm (1/4")
Length of Stroke	18 mm (11/16")
Strokes Per Minute (SPM)	0 - 3,100
Vibration Level	Cutting Wood: 8.0 m/s ² Cutting Sheet Metal: 5.0 m/s ²
Sound Pressure Level	82 dB(A)
Sound Power Level	93 dB(A)
Dimensions (L x W x H)	214x75x202 mm (8-3/8"x2-15/16"x8")
Net weight	1.9 kg (4.1 lbs)
Power supply cord	2.0 m (6.6 ft.)



M4302

CB: 411 MT Series

ELECTRIC JIG SAW

Tool Available in:
* M4302B
* M4302M



Continuous rating input	450W
Max Cutting Capacity at 90°	Wood: 55 mm (2-3/16") Steel: 6 mm (1/4")
Length of Stroke	26 mm (1")
Strokes Per Minute (SPM)	0 - 3,100
Vibration Level	Cutting Boards: 6.5 m/s ² Cutting Sheet Metal: 7.5 m/s ²
Sound Pressure Level	88 dB(A)
Sound Power Level	99 dB(A)
Dimensions (L x W x H)	219x85x191 mm (8-5/8"x3-3/8"x7-1/2")
Net weight	2.5 kg (5.5 lbs.)
Power supply cord	2.0 m (6.6 ft.)



M9800

CB: 459 MT Series

ELECTRIC MULTI TOOL

Tool Available in:
* M9800BKX2
* M9800B



Continuous Rating Input	200W
Oscillations Per Minute (OPM)	15,000 - 22,000
Oscillation Angle	Left: 1.6° Right: 1.6° Total: 3.2°
Circumference of Grip Portion	195 mm (7-5/8")
Shank Type	Multi Tool: CIS
Vibration Level	Sanding: 2.5 m/s ² Scraping: 9.5 m/s ²
Sound Pressure Level	Sanding: 78 dB(A) Scraping: 78 dB(A)
Dimensions (L x W x H)	283 x 68 x 98 mm (11-1/8 x 2-11/16 x 3-7/8")
Net weight	1.2 - 1.3 kg (2.7 - 3.0 lbs.)
Power supply cord	2.0 m (6.6 ft.)



M0900

CB: 459 MT Series

ELECTRIC ANGLE GRINDER

Tool Available in:
* M0900B



Continuous rating input	540W
Wheel Diameter	100 mm (4")
No Load Speed (RPM)	12,000
Dimensions (L x W x H)	251x118x97 mm (9-7/8"x4-5/8"x3-13/16")
Net weight	1.65 kg (3.64 lbs)
Power supply cord	2.0 m (6.6 ft.)



M0910

CB: 459 MT Series

ELECTRIC ANGLE GRINDER

Tool Available in:
* M0910B



Continuous rating input	540W
Wheel Diameter	100 mm (4")
No Load Speed (RPM)	12,000
Dimensions (L x W x H)	251x118x93 mm (9-7/8"x4-5/8"x3-5/8")
Net weight	1.64 kg (3.62 lbs)
Power supply cord	2.0 m (6.6 ft.)



M0920

CB: 203 MT Series

ELECTRIC ANGLE GRINDER

Tool Available in:
* M0920M



Continuous rating input	2,200W
Wheel Diameter	180 mm (7")
No Load Speed (RPM)	8,500
Vibration Level	Surface Grinding: 6.5 m/s ²
Sound Pressure Level	91 dB(A)
Sound Power Level	102 dB(A)
Dimensions (L x W x H)	439x200x141 mm (17-1/4"x7-7/8"x5-9/16")
Net weight	5.0 kg (11.0 lbs)
Power supply cord	2.0 m (6.6 ft.)



M9000

CB: 204 MT Series

ELECTRIC ANGLE GRINDER

Tool Available in:
* M9000B
* M9000M



Continuous Rating Input	2,000W
Wheel Diameter	180 mm (7")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Vibration Level	Surface Grinding: 5 m/s ²
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Dimensions (L x W x H)	466 x 200 x 138 mm (18-3/8 x 7-7/8 x 5-7/16")
Net weight	5.4 kg (12 lbs.)
Power supply cord	2.0 m (6.6 ft.)



M9002

CB: 303 MT Series

ELECTRIC ANGLE GRINDER

Tool Available in:
* M9002B



Continuous Rating Input	1,050W
Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	11,000
Vibration Level	Surface Grinding: 9 m/s ²
Vibration K Factor	Surface Grinding: 1.5 m/s ²
Sound Pressure Level	91 dB(A)
Sound Power Level	102 dB(A)
Noise K Factor	3 dB(A)
Dimensions (L x W x H)	351 x 140 x 124 mm (14-1/4 x 5-1/2 x 4-7/8")
Abrasive Grinding Wheel Diameter	125 mm (5")
Net weight	2.8 kg (6.1 lbs.)
Power supply cord	2.0 m (6.6 ft.)



M9513

CB: 325 MT Series

ELECTRIC ANGLE GRINDER

Tool Available in:
* M9513B



Continuous Rating Input	850W
Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	11,000
Dimensions (L x W x H)	273 x 118 x 101 mm (10-3/4 x 4-5/8 x 4")
Abrasive Grinding Wheel Diameter	100 mm (4")
Thread	M10x1.5
Net weight	1.8 kg (4 lbs.)
Power supply cord	2.0 m (6.6 ft.)



MT910

CB: 411 Maktec

ELECTRIC DIE GRINDER



Continuous Rating Input	260W
Collet Size	6 mm (1/4")
Wheel Diameter	38 mm (1-1/2") 24 mm / CN
No Load Speed (RPM)	25,000
Dimensions (L x W x H)	328 x 63 x 63 mm (13 x 2-1/2 x 2-1/2")
Mandrel (Shank) Length	46 mm
Net weight	1.2 kg (2.6 lbs.)
Power supply cord	2.0 m (6.6 ft.)



M9400

CB: 153 MT Series

ELECTRIC BELT SANDER
 Tool Available in:
 * M9400B



Continuous Rating Input	940W
Belt Size	100 x 610 mm (4 x 24") X: 100 mm (4") Y: 610 mm (24")
Belt Speed	380 mm/min (1,250 ft/min)
Vibration Level	Sanding Metal Plate: 2.5 m/s ² or less
Vibration K Factor	Sanding Metal Plate: 1.5 m/s²
Sound Pressure Level	87 dB(A)
Sound Power Level	98 dB(A)
Noise K Factor	3 dB(A)
Dimensions (L x W x H)	354 x 175 x 169 mm (14 x 6-7/8 x 6-5/8")
Net weight	6.2 kg (13.7 lbs.)
Power supply cord	2.0 m (6.6 ft)



M9200

CB: 419 MT Series

ELECTRIC FINISHING SANDER
 Tool Available in:
 * M9200B
 * M9002M



Continuous Rating Input	180W
Pad Size	112 x 102 mm (4-3/8 x 4")
Pad Type Clamp	YES
Pad Type Hook & Loop	NO
Sheet Size	1/4
Abrasive Paper Size	114 x 140 mm (4-1/2 x 5-1/2")
Paper Size Clamp	X: 114 mm (4-1/2") Y: 140 mm (5-1/2")
Orbits per minute (OPM)	14,000
Vibration Level	Sanding Metal Plate: 4.5 m/s ²
Vibration K Factor	Sanding Metal Plate: 1.5 m/s ²
Sound Pressure Level	79 dB(A)
Dimensions (L x W x H)	110 x 112 x 133 mm (4-5/16 x 4-3/8 x 5-1/4")
Net weight	0.9 kg (2 lbs.)
Power supply cord	2.0 m (6.6 ft)



M9201

CB: 64 MT Series

ELECTRIC FINISHING SANDER
 Tool Available in:
 * M9201B



Continuous Rating Input	180W
Pad Size	93 x 185 mm (3-5/8 x 7-1/4")
Pad Type Clamp	YES
Pad Type Hook & Loop	NO
Sheet Size	1/3
Abrasive Paper Size	93 x 228 mm (3-5/8 x 9")
Paper Size Clamp	X: 93 mm (3-5/8") Y: 228 mm (9")
Orbits per minute (OPM)	12,000
Vibration Level	Sanding Metal Plate: 6 m/s ²
Vibration K Factor	Sanding Metal Plate: 1.5 m/s ²
Sound Pressure Level	74 dB(A)
Dimensions (L x W x H)	214 x 92 x 147 mm (8-3/8 x 3-5/8 x 5-3/4")
Net weight	1.4 kg (3.1 lbs.)
Power supply cord	2.0 m (6.6 ft)



M9202

CB: 419 MT Series

ELECTRIC RANDOM ORBIT SANDER
 Tool Available in:
 * M9202B



Continuous Rating Input	240W
Pad Size	123 mm (4-7/8")
Abrasive Disc Size	125 mm (5")
Orbits per minute (OPM)	12,000
Strokes Per Minute (SPM)	24,000
Orbit Diameter	2.8 mm (1/8")
Dimensions (L x W x H)	127 x 123 x 142 mm (5 x 4-7/8 x 5-5/8")
Brush Pad Capacity	123 mm (4-7/8")
Disc Power Diameter	125 mm (5")
Net weight	1.1 kg (2.4 lbs.)
Power supply cord	2.0 m (6.6 ft)



M1100

CB: 303 MT Series

ELECTRIC PLANER
 Tool Available in:
 * M1100KB



Continuous rating input	750W
Planing Width	82 mm (3-1/4")
Planing Depth	3 mm (1/8")
Max Shipping	20 mm (3/4")
No Load Speed (RPM)	18,000
Vibration Level	Planing Softwood: 2.5 m/s ² or less
Sound Pressure Level	81 dB(A)
Sound Power Level	102 dB(A)
Dimensions (L x W x H)	390x175x140 mm (15-3/8"x6-7/8"x5-1/2")
Net weight	4.6 kg (10.2 lbs.)
Power supply cord	2.0 m (6.6 ft)



M1902

CB: 41 MT Series

ELECTRIC PLANER
 Tool Available in:
 * M1902B



Continuous rating input	500W
Planing Width	82 mm (3-1/4")
Planing Depth	1 mm (1/32")
Max Shipping	9 mm (11/32")
No Load Speed (RPM)	16,000
Vibration Level	Planing Softwood: 3.0 m/s ²
Sound Pressure Level	84 dB(A)
Sound Power Level	95 dB(A)
Dimensions (L x W x H)	285x157x160 mm (11-1/4"x6-3/16"x6-5/16")
Net weight	2.6 - 2.7 kg (5.7 - 6.0 lbs.)
Power supply cord	2.0 m (6.6 ft)



M3700

CB: 411 MT Series

ELECTRIC TRIMMER
 Tool Available in:
 * M3700B



Continuous rating input	530W
Collet Capacity	6 mm or 1/4"
No Load Speed (RPM)	35,000
Plunge Capacity	0 - 42 mm (0 - 1-5/8")
Vibration Level	Rotation without Load: 2.5 m/s ² or less
Sound Pressure Level	83 dB(A)
Sound Power Level	94 dB(A)
Dimensions (L x W x H)	82x90x199 mm (3-1/4"x3-1/2"x7-7/8")
Net weight	1.4 kg (3.1 lbs.)
Power supply cord	2.0 m (6.6 ft)



M3702

CB: 999 MT Series

ELECTRIC TRIMMER
 Tool Available in:
 * M3702B



Continuous Rating Input	530W
Collet Size	6 mm (1/4")
Base Inner	35 mm (1-3/8")
No Load Speed (RPM)	35,000
Plunge Capacity	0 - 42 mm (0 - 1-5/8")
Vibration Level	Rotation w/o Load: 2.5 m/s ² or less Rotation w/ Load: 1.5 m/s ²
Sound Pressure Level	83 dB(A)
Sound Power Level	94 dB(A)
Noise K Factor	3 dB(A)
Dimensions (L x W x H)	82 x 90 x 211 mm (3-1/4 x 3-1/2 x 8-5/16")
Net weight	1.5 kg (3.3 lbs.)
Power supply cord	2.0 m (6.6 ft)



M3600

CB: 211 MT Series

ELECTRIC ROUTER
 Tool Available in:
 * M3600B
 * M3600M



Continuous rating input	1,650W
Collet Capacity	12 mm or 1/2"
Plunge Capacity	0 - 60 mm (0 - 2-3/8")
No Load Speed (RPM)	22,000
Vibration Level	Cutting Grooves in MDF: 2.5 m/s ²
Sound Pressure Level	86 dB(A)
Sound Power Level	97 dB(A)
Dimensions (L x W x H)	284x148x300 mm (11-1/8"x5-7/8"x11-3/4")
Net weight	5.5 kg (12.2 lbs.)
Power supply cord	2.0 m (6.6 ft)



M3602

CB: 203 MT Series

ELECTRIC ROUTER
 Tool Available in:
 * M3602B
 * M3602M



Continuous Rating Input	1,650W
Collet Capacity	12 mm or 1/2 lbs.
Collet Size	6.8, 12 mm (1/4, 3/8, 1/2")
Plunge Capacity	0 - 60 mm (0 - 2-3/8")
No Load Speed (RPM)	22,000
Vibration Level	Cutting Grooves in MDF: 3.1 m/s ²
Vibration K Factor	Cutting Grooves in MDF: 1.5 m/s ²
Sound Pressure Level	84 dB(A)
Sound Power Level	95 dB(A)
Noise K Factor	3 dB(A)
Dimensions (L x W x H)	148 x 284 x 300 mm (5-7/8 x 11-1/8 x 11-3/4")
Net weight	5.7 kg (12.6 lbs.)
Power supply cord	2.0 m (6.6 ft)



Makita - A Global Brand

Makita have established directly operated business bases in about 50 countries around the world, and have upgraded our sales network in over 170 countries and after-sales service capabilities to become one of the leading companies in our industry. In addition, Makita is producing power tools and OPE in China, Romania, Thailand, U.K., Brazil, U.S. and Germany. Currently, about 90% of our group's manufacturing work in terms of production volume is carried out overseas.

Makita's worldwide sales and service network, as well as the stable, high production quality ensured at its plants worldwide, are the embodiment of the Makita brand.

No. of Sales and Services Bases

319

bases

NORTH AMERICA

4 companies



Makita Werkzeug GmbH
(in Germany)



Makita Ukraine LLC

EUROPE

27 companies

ASIA

10 companies

JAPAN

19 branches **121** sales offices



Makita Corporation (in Japan)

The Middle East and Africa

2 companies



Makita U.S.A. Inc.

Central and South America

6 companies

Oceania

2 companies

- Sales and Service Bases
- Production Bases

JAPAN

Makita Corporation Headquarters



JAPAN

Okazaki Plant



U.S.A.

U.S. Plant



UNITED KINGDOM

U.K. Plant



ROMANIA

Romania Plant



GERMANY

Germany Plant



BRAZIL

Brazil Plant



CHINA

China Plant (MCC)



CHINA

China Plant (MKC)



THAILAND

Thailand Plant



Makita®

mt



maktec®
by Makita

AVAILABLE AT:

LAST UPDATED ON:

JUNE 2022
PRINTED IN THE PHILIPPINES